



## Zhongshan Caprazze Photoelectric Technology Co.,Ltd

ADD:NO.13 Yifeng Middle Road,Ji Dong Er CommunityXiaolan Town, Zhongshan, Guangdong Province, China

TEL:+86-760-22262285/22268810

FAX:+86-760-22267963

EMAIL:admin@caprazze.com

WEBSITE: www.caprazze.com

Legal Disclaimer: The appearances and parameters of the products listed in this book are for reference only and do not constitute any form of contract. The company reserves the right to modify or cancel the relevant parameters of the book at any time without prior notice. The copyright of this catalogue belongs to Zhongshan Caprazze Photoelectric Technology Co.,Ltd. If you have any questions, please call the customer service hotline.



PROJECT-BUSINESS-PUBLIC LIGHTING PRODUCT SUMMARY



Zhongshan CAPRAZZE is an OEM and LED lighting and light parts manufacturer. Main producing various indoor; outdoor, & solar commercial & industrial lights. Founded in late 2015 by a group of Chinese and European investors with a vast experience in the LED lighting field; built on a 5000 sqm factory in Xiaolan town Zhongshan city, it benefits from this strategic location close to ports and areas like Guangzhou; Foshan; Shenzhen And HK that are hubs to several LED source manufacturers & technology developers. Moreover CAPRAZZE has its own R&D department with an advanced testing center striving to ensure continuous technical development and innovation. All CAPRAZZE products are produced in accordance with IEC standards and are CE/LVD& RoHS certified. Currently CAPRAZZE exports finished goods to more than 20 countries globally; in addition of being a strategic partner and the backbone of several newly established SKD & CKD factories in North Africa, Central Asia and Eastern Europe.

## CONTENTS\_

<b>03-04</b>	Small LED Bulb Series
<b>05-06</b>	GU10-MR16 Series
<b>07-08</b>	A Bulb Series
<b>09-10</b>	T Bulb Series
<b>11-12</b>	Panel Light Series
<b>13-14</b>	Panel Light No Bourder Series
<b>15-16</b>	Modular Panel Back-lighting Series
<b>17-18</b>	Flood Light Series
<b>19-20</b>	UFO Highbay Series
<b>21-22</b>	LED Street Light Series
<b>23-24</b>	LED Street Light COB Series
<b>25-26</b>	LED Highbay Series



### LED Candle Bulb Series Specification

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-C37	3W	Φ37*100	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-C37	4W	Φ37*100	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-C37	5.5W	Φ37*100	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-C37	7W	Φ37*100	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22



### LED G45 Bulb Series Specification

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-G45	3W	Φ45*82	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-G45	4W	Φ45*82	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-G45	5.5W	Φ45*82	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22
CPZ-G45	7W	Φ45*82	PC cover+PBT+6063AL	AC85-265V	0.5	80	> 80LM/W	E14/E27/B22



### LED Small T Bulb Series

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-T37	9W	Φ37*115	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	GU5.3 /GU10
CPZ-T44	15W	Φ44*139	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	GU5.3 /GU10



- High Quality
- High Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



### LED Gu10 Bulb Series Specification

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-Gu10	4W	Φ50*56	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	GU5.3 /Gu10
CPZ-Gu10	6W	Φ50*56	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	GU5.3 /Gu10



### LED MR16 Bulb Series Specification

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-MR16	4W	Φ50*52	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	Mr16
CPZ-MR16	6W	Φ50*52	PC cover+AL	AC85-265V	0.5	80	> 90LM/W	Mr16



### LED A Bulb Series



A bulb Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-A50	5W	Φ50*90	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A60	7W	Φ60*118	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A60	9W	Φ60*118	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A65	12W	Φ65*125	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A70	15W	Φ70*128	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A80	18W	Φ80*146	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-A95	24W	Φ95*165	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22



### LED E Bulb Series

A bulb Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-E100	30W	Φ94*215	PC cover+PBT+6063AL	AC85-265V	0.5	80	>120LM/W	E27/B22
CPZ-E120	40W	Φ105*235	PC cover+PBT+6063AL	AC85-265V	0.5	80	>120LM/W	E27/B22
CPZ-E140	50W	Φ120*275	PC cover+PBT+6063AL	AC85-265V	0.5	80	>120LM/W	E27/B22



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



### LED T Bulb Series

Model	Power	Size(mm)	Material	Voltage	PF	CRI	Lumens	Lamp Base
CPZ-T50	5W	Φ50*100	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T60	7W	Φ60*118	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T60	9W	Φ60*118	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T70	13W	Φ70*130	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T80	18W	Φ80*145	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T100	28W	Φ100*185	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T115	32W	Φ115*205	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T120	36W	Φ120*235	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22
CPZ-T140	45W	Φ140*250	PC cover+PBT+6063AL	AC85-265V	0.5	80	>100LM/W	E27/B22



- High Quality
- Thick Aluminum + PC
- Isolate of Power
- Constant Current IC Driver
- High Heat Dissipation Performance





### LED Surface Panel Light Series Specification

Model	Power	Size(mm)	Cut hole(MM)	Shape	Voltage	PF	CRI	Lumens
CPZ-SF-6R	3W	ø90mm	ø80	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-6S		90x90	80x80	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-9R	6W	ø120	ø110	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-9S		120x120	110x110	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-12R	9W	ø145	ø130	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-12S		145x145	130x130	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-18R	12W	ø180	ø160	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-18S		180x180	160x160	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-24R	15W	ø180	ø160	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SF-24S		180x180	160x160	SQ	AC 85-265V	0.5	80	> 95LM/W



### LED Slim Panel Light Series Specification

Model	Power	Size(mm)	Cut hole(MM)	Shape	Voltage	PF	CRI	Lumens
CPZ-SLP-3R	3W	ø90mm	ø80	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-3S		90x90	80x80	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-6R	6W	ø120	ø110	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-6S		120x120	110x110	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-9R	9W	ø145	ø130	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-9S		145x145	130x130	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-12R	12W	ø180	ø160	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-12S		180x180	160x160	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-15R	15W	ø180	ø160	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-15S		180x180	160x160	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-18R	18W	ø225	ø210	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-18S		225x225	210x210	SQ	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-24R	24W	ø300	ø280	RD	AC 85-265V	0.5	80	> 95LM/W
CPZ-SLP-24S		300x300	/	SQ	AC 85-265V	0.5	80	> 95LM/W



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance

- High Quality
- Thick Aluminium +3%
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



### LED Panel Light No Border Series Specification

Model	Power	Size(mm)	Cut hole(MM)	Shape	Material	Voltage	CRI	Lumens
CPZ-NBP-12R	12W	ø90*H16	ø70	RD	Die casting AL with PC plastic	AC 85-265V	80	>100LM/W
CPZ-NBP-12S		90ø90x16	70x70	SQ		AC 85-265V	80	>100LM/W
CPZ-NBP-15R	18W	ø120*H16	ø105	RD		AC 85-265V	80	>100LM/W
CPZ-NBP-15S		120x120x16	105x105	SQ		AC 85-265V	80	>100LM/W
CPZ-NBP-18R	24W	ø170*H16	ø155	RD		AC 85-265V	80	>100LM/W
CPZ-NBP-18S		170x170x16	155x155	SQ		AC 85-265V	80	>100LM/W
CPZ-NBP-24R	36W	ø225*H17	ø205	RD		AC 85-265V	80	>100LM/W
CPZ-NBP-24S		225x225x17	205x205	SQ		AC 85-265V	80	>100LM/W







### LED Modular Panel Back-Lighting Series Specification

Model	Power	Size(mm)	Voltage	CRI	Material	PF	Lumens
CPZ-MPB-3030	18/24 W	295X295	AC 85-265V	80	Welded Aluminum Frame+Metal Back Cover+PMMA Chip Lens	0.9	85LM/W
CPZ-MPB-3060	24/36 W	295X595	AC 85-265V	80		0.9	85LM/W
CPZ-MPB-30120	36/48 W	295X1195	AC 85-265V	80		0.9	85LM/W
CPZ-MPB-6060	36/40/48/60W	595X595	AC 85-265V	80		0.9	85LM/W
CPZ-MPB-60120	48/60/72W	595X1195	AC 85-265V	80		0.9	85LM/W



Optional surface mount frame



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



### LED Flood Light Series Specification

Model	Power	Size(mm)	Voltage	CRI	Material	IP	Lumens
CPZ-FL-050W	50W	216*188*55	AC 85-265V	80	Die casting AL	65	>100LM/W
CPZ-FL-100W	100W	273*244*60	AC 85-265V	80		65	>100LM/W
CPZ-FL-150W	150W	314*330*61	AC 85-265V	80		65	>100LM/W
CPZ-FL-200W	200W	420*346*66	AC 85-265V	80		65	>100LM/W
CPZ-FL-300W	300W	463*450*69	AC 85-265V	80		65	>100LM/W



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance

- High Quality
- Thick Aluminum
- Isolated Power
- Constant Current Driver
- High Heat Dissipation Performance



### LED UFO Highbay Lamp Series Specification

Model	Power	Size(mm)	Voltage	CRF	Material	IP	Lumens
CPZ-UFO-100W	100W	278*40mm	AC 85-265V	80	Die casting AL	65	> 130LM/W
CPZ-FUO-150W	150W	328*40mm	AC 85-265V	80		65	> 130LM/W
CPZ-UFO-200W	200W	388*40mm	AC 85-265V	80		65	> 130LM/W





### LED Street Light SMD New Module Series Specification

Model	Power	Size(mm)	Voltage	CRI	Material	IP	Lumens
CPZ-STSM-D-100W	100W	264*280*115mm	AC 85-265V	80	Die casting AL	65	120LM/W
CPZ-STSM-D-150W	150W	353*280*115mm	AC 85-265V	80		65	120LM/W
CPZ-STSM-D-200W	200W	442*280*115mm	AC 85-265V	80		65	120LM/W
CPZ-STSM-D-240W	240W	531*280*115mm	AC 85-265V	80		65	120LM/W
CPZ-STSM-D-300W	300W	620*280*115mm	AC 85-265V	80		65	120LM/W



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



- High Quality
- Thick Aluminium + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance



### LED Street Light COB Series Specification

Model	Power	Size(mm)	Voltage	CRI	Material	IP	Lumens
CPZ-STCOB-50W	50W	500*215*100mm	AC 85-265V	80	Die casting AL	65	> 110LM/W
CPZ-STCOB-80W	80W	620*262*110mm	AC 85-265V	80		65	> 110LM/W
CPZ-STCOB-100W	100W	725*275*120mm	AC 85-265V	80		65	> 110LM/W
CPZ-STCOB-150W	150W	890*310*115mm	AC 85-265V	80		65	> 110LM/W
CPZ-STCOB-200W	200W	950*350*115mm	AC 85-265V	80		65	> 110LM/W





### LED Highbay Lamp Series Specification

Model	Power	Size(mm)	Voltage	CRI	Material	Weight (kg)	Lumens
CPZ-HBY-200W	200W	159*260*90mm	AC 85-265V	80	Die casting AL	5.1kg	120LM/W
CPZ-HBY-300W	300W	231*260*90mm	AC 85-265V	80		5.9kg	120LM/W
CPZ-HBY-400W	400W	303*260*90mm	AC 85-265V	80		6.9kg	120LM/W
CPZ-HBY-500W	500W	231*260*129mm	AC 85-265V	80		7.9kg	120LM/W
CPZ-HBY-600W	600W	303*260*129mm	AC 85-265V	80		9.5kg	120LM/W
CPZ-HBY-800W	800W	387*270*157mm	AC 85-265V	80		10kg	120LM/W
CPZ-HBY-1000W	1000W	446*270*157mm	AC 85-265V	80		11kg	120LM/W



- High Quality
- Thick Aluminum + PC
- Isolated Power
- Constant Current IC Driver
- High Heat Dissipation Performance

